

1 **PROPOSAL 3-122 (2009)**
2
3

4
5 **SCOPE: Part 2, Commentary Chapter 22**
6

7
8
9 **PROPOSAL FOR CHANGE:**

10
11 **Add Chapter 22 to Part 2, of the 2009 Commentary:**

12
13 *Proposed Chapter is attached. Text is not underlined to allow easier*
14 *review.*

15
16 **REASON FOR PROPOSAL:**

17
18 One of the basic tasks of the 2009 NEHRP *Provisions* update is to develop a viable
19 commentary to Part 1. Since Part 1 adopts ASCE 7-05 and lists any exceptions to it, the
20 Commentary is developed in accordance with the format and sections of ASCE 7-05.
21

Chapter 22

SEISMIC GROUND MOTION AND LONG-PERIOD TRANSITION MAPS

SEISMIC GROUND MOTION MAPS

The 2005 edition of ASCE 7 continues to use contour maps of spectral response acceleration (Figures 22-1 through 22-14). The spectral acceleration design maps were prepared by the United States Geological Survey (USGS) based on USGS probabilistic maps of the 48 conterminous states (2002), Alaska (1998), Hawaii (1998), and Puerto Rico/Virgin Islands (2003) with modifications based on the 1997 recommendations of the Building Seismic Safety Council. The maps of the 48 states and Puerto Rico/Virgin Islands have been updated from the 2002 edition of the standard. The maps of Alaska, Hawaii, Guam, and Tutuila are unchanged from the 2002 edition.

The USGS also has developed a companion software program that calculates location-specific spectral values based on latitude and longitude or zip code; use of zip codes is discouraged in regions where ground-motion values vary substantially over a short distance. The calculated values are based on the data used to prepare the maps shown as Figures 22-1 through 22-14. The spectral values should be adjusted for Site Class effects using the Site Classification Procedure in Section 20 and the site coefficients in Section 11.4. Latitude and longitude for a given address can be found at a variety of websites. The companion software program may be accessed at the USGS website (<http://earthquake.usgs.gov/research/hazmaps/>) by clicking on “Seismic Design Values for Buildings.” The software program should be used to establish spectral values for design because the maps found in ASCE 7 and at websites are too small to provide accurate spectral values for many sites.

LONG-PERIOD TRANSITION MAPS

The maps of the Long-Period Transition Period, T_L , (Figures 22-15 through 22-20) were introduced in ASCE 7-05. They were prepared by the USGS based on the 2003 recommendations of the BSSC. See Section C11.4.5 for a discussion of the technical basis of these maps. The value of T_L obtained from these maps is used in Equation 11.4-7 to determine values of S_a for periods greater than T_L .

The exception in Section 15.7.6.1, regarding the calculation of S_{ac} , the convective response spectral acceleration for tank response, is intended to provide the user the option of computing this acceleration with three different types of site-specific procedures: (1) the procedures in Chapter 21, provided they cover the natural period band containing T_c , the fundamental convective period of the tank-fluid system, (2) ground-motion simulation methods using seismological models, and (3) analysis of representative accelerogram data. Elaboration of these procedures is provided below.

With regard to the first procedure, attenuation equations have been developed for the western United States (Next Generation Attenuation, Power et al., 2006, 2008) and for the central and eastern United States (e.g., Somerville et al., 2001) that cover the period band, 0 to 10 seconds. Thus, for $T_c \leq 10$ seconds, the fundamental convective period range for nearly all storage tanks,

1 these attenuation equations can be used in the same PSHA/DSHA procedures described in
2 Chapter 21 to compute $S_a(T_c)$. The 1.5 factor in Equation 15.7-11, which converts a 5 percent
3 damped spectral acceleration to a 0.5 percent damped value, could then be applied to obtain S_{ac} .
4 Alternatively, this factor could be established by statistical analysis of 0.5 percent damped and 5
5 percent damped response spectra of accelerograms representative of the ground motion expected
6 at the site.

7
8 In some regions of the United States, such as Pacific Northwest and southern Alaska, where
9 subduction-zone earthquakes dominate the ground-motion hazard, attenuation equations for these
10 events only extend to periods between 3 and 5 s, depending on the equation. Thus, for tanks with
11 T_c greater than these periods, other site-specific methods are required.

12
13 The second site-specific method to obtain S_a at long periods is simulation through the use of
14 seismological models of fault rupture and wave propagation (Graves and Pitarka, 2004; Hartzell
15 and Heaton, 1983; Hartzell et al., 1999; Liu et al., 2006; Zeng et al., 1994). These models could
16 range from simple seismic source-theory and wave-propagation models, which currently form the
17 basis for many of the attenuation equations used in the central and eastern United States for
18 example, to more complex numerical models that incorporate finite fault rupture for scenario
19 earthquakes and seismic wave propagation through 2-D or 3-D models of the regional geology,
20 which may include basins. These models are particularly attractive for computing long-period
21 ground motions from great earthquakes ($M_w \geq \sim 8$) because ground-motion data are limited for
22 these events. Furthermore, the models are more accurate for predicting longer-period ground
23 motions because (1) seismographic recordings may be used to calibrate these models, and (2) the
24 general nature of the 2-D or 3-D regional geology is typically fairly well resolved at these periods
25 and can be much simpler than would be required for accurate prediction of shorter period
26 motions.

27
28 A third site-specific method is the analysis of the response spectra of representative
29 accelerograms that have accurately recorded long-period motions to periods greater than T_c . As
30 T_c increases, the number of qualified records decreases. However, as digital accelerographs
31 continue to replace analog accelerographs, more recordings with accurate long-period motions
32 will become available. Nevertheless, a number of analog and digital recordings of large and great
33 earthquakes are available that have accurate long-period motions to 8 seconds and beyond.
34 Subsets of these records, representative of the earthquake(s) controlling the ground-motion hazard
35 at a site, can be selected. The 0.5 percent damped response spectra of the records can be scaled
36 using seismic source theory to adjust them to the magnitude and distance of the controlling
37 earthquake. The levels of the scaled response spectra at periods around T_c can be used to
38 determine S_{ac} . If the subset of representative records is limited, then this method should be used
39 in conjunction with the aforementioned simulation methods.

40 41 REFERENCES

- 42 Graves, R.W., and Pitarka, A., 2004. "Broadband Time History Simulation using a Hybrid
43 Approach," Proc. 13th World Conf. Earthq. Eng., Vancouver, Canada, paper no. 1098.
- 44 Hartzell, S., and Heaton, T., 1983. "Inversion of Strong Ground Motion and Teleseismic
45 Waveform Data for the Fault Rupture History of the 1979 Imperial Valley, California
46 Earthquake," Bull. Seism. Soc. Am., v. 73, p. 1553-1583.

- 1 Hartzell, S., Harmsen, S., Frankel, A., and Larsen, S., 1999. "Calculation of Broadband Time
2 Histories of Ground Motion: Comparison of Methods and Validation Using Strong Ground
3 Motion from the 1994 Northridge Earthquake," Bull. Seism. Soc. Am., v. 89, p. 1484-1504.
- 4 Liu, P., Archuleta, R.J., and Hartzell, S.H., 2006. "Prediction of Broadband Ground-Motion Time
5 Histories: Hybrid Low/High-Frequency Method with Correlated Random Source Parameters,"
6 Bull. Seism. Soc. Am., v. 96, p. 2118–2130.
- 7 Power, M., Chiou, B., Abrahamson, N., Bozorgnia, Y., Shantz, T., and Roblee, C., 2008. "An
8 Overview of the NGA Project, Earthquake Spectra Special Issue on the Next Generation of
9 Ground Motion Attenuation (NGA) Project," Earthquake Engineering Research Institute, March.
- 10 Power, M., Chiou, B., Abrahamson, N., and Roblee, C., 2006. "The Next Generation of Ground
11 Motion Attenuation Models," Proceedings of the 100th Anniversary Earthquake Conference
12 Commemorating the 1906 San Francisco Earthquake, San Francisco, CA, April.
- 13 Zeng, Y., Anderson, J.G., and Yu, G., 1994. "A Composite Source Model for Computing
14 Synthetic Strong Ground Motions," Geophys. Res. Lett. v. 21, p. 725-728.
15
16
17